Semi-Automatic Stretch Wrapper

ROTARY 708

SEMI AUTOMATIC STRETCH WRAPPER

1 YEAR WARRANTY

Ideal for wrapping heavy and unstable loads.

The Rotary 708 with CUBE technology is the most innovative rotary arm stretch wrapper on the market. It is also the easiest to use, thanks to its intuitive seven (7) inch color touchscreen.

- CUBE TECHNOLOGY REDUCES FILM USAGE BY 30% TO 55%.
- INTUITIVE ICON-DRIVEN TOUCHSCREEN MAKES IT EASY TO SET UP THE CORRECT PARAMETERS FOR WRAPPING EACH LOAD.
- YOU CONTROL CONTAINMENT FORCE, ROTATION SPEED, ROPING AND BANDING AT NINE (9) LEVELS ON EACH LOAD.
- REMOTE CONTROL INCLUDED

PERFORMANCE FEATURES:

CONTROL PANEL

The control panel has been newly designed, adopting it to a touch screen. Thanks to the large 7"color touch screen this new panel allows you to create programs simply and immediately. It is supplied with more memory to record up to 12 different programs (6+6 with Multilevel Control).

PVS CARRIAGE

The PVS Carriage with powered stretch system controlled by two independent motors. Stretch ratio adjustable from panel board from 150% up to 400%. Force to the load controlled by patented electronic device and adjustable from panel board.

HORIZONTAL ROTATING EXTENDABLE ARM

First adjustable rotating arm machine. Adjust length of rotating arm to wrap products with maximum dimensions 55" x 55". Reduce by adjusting minimum length to wrap products only 16" x 16".

ROTARY 708 SPEC SHEET

Load Capacity:
-Maximum Load Dimensions:
55” W x 55” L x 78” H
-Maximum Load Weight: Unlimited

Film Delivery System
-Power Variable Stretch 150 – 400%
-Containment Force: Load Cell
-Film Carriage Motor: 1/3 HP VAC
-Height Sensing: Automatic photo eye
-Film Threading: Patented S-Pattern
-Corner Compensation: Load Cell
-Standard Film Width – 20” (30” option)

Performance Criteria
-Production Speed: Up to 35 LPH
-Wrap Arm Speed: 12 RPM
-Rotary Arm Drive: 1 HP VAC
-Remote Control: Standard

Utility Requirements
-Voltage: 120V, 13.2 amps, 60 Hz, 1 PH

Safety Features
-Safety Bumper Warning Light
-Safety Alarm
-CE Compliant, UL, CUL

Operator Interface
-Touch screen HMI control panel
-12 programmable wrapping menus

ROBOPACUSA.COM

INFO.US@ROBOPAC.COM