

Semi-Automatic Stretch Wrapper

# TECHNOPLAT 708 CS

**SEMI AUTOMATIC  
STRETCH WRAPPER**



**ROBOPAC**  
USA

## PERFORMANCE FEATURES:

### COLOR TOUCH SCREEN

The high performance 7-inch color touch screen with icons specifically designed and created by Robopac has led to the implementation of the **MULTILEVEL CONTROL** function.

### CLAMP, CUTTING AND SPREADING UNIT


Technoplat CS is equipped with automatic clamp, cutting, and spreading unit.



**Increase productivity and keep your operators safe by keeping them on the fork truck.**

- HEAVY DUTY CLAMP, CUT AND SPREADING SYSTEM
- KEEP DRIVER IN THE DRIVER'S SEAT WHERE THEY CAN BE THE MOST PRODUCTIVE.
- 110" WRAP HEIGHT STANDARD
- REMOTE CONTROL INCLUDED
- CUBE TECHNOLOGY DELIVERS THE RIGHT AMOUNT OF FILM AT EXACTLY THE RIGHT POSITION WITH EXACTLY THE RIGHT CONTAINMENT FORCE
- MULTI-LEVEL VARIABLE CONTAINMENT FORCE IS OPTIMIZED AT EACH LEVEL AND IS ADJUSTABLE UP TO NINE (9) TIMES ON EACH LOAD.
- CUBE TECHNOLOGY WILL REDUCE YOUR FILM USAGE BY 30% - 55%.
- OPTION FOR R CONNECT (INCLUDES 36-MONTH INITIAL CELLULAR DATA PLAN).

# TECHNOPLAT 708 CS SPEC SHEET



## Load Capacity:

- Turntable Size:  
**65" Diameter**
- Maximum Load  
**Dimensions:  
40" W x 48" L x 110" H**
- Maximum Load Height:  
**110" Standard**
- Maximum Load Weight:  
**4400 lbs.**



## Film Delivery System

- Multi-Level Variable **100 – 400%**
- Containment Force: Variable  
**Load Cell**
- Film Carriage Motor: **½ HP VAC**  
**Chain Driven**
- Height Sensing: Automatic via  
**photocell**
- Film threading: patented S-  
**Pattern**
- Corner Compensation: **Load Cell**
- Standard Film Width – **20" (30"**  
**option)**



## Performance Criteria

- Production Speed:  
**Up to 40 LPH**
- Turntable Speed:  
**5 – 15 RPM**
- Turntable Drive:  
**1 HP VAC**



## Utility Requirements

- Voltage:  
**120V, 12 amps, 60**  
**Hz, 1 PH**
- Air:  
**60 PSI**
  
- NEMA 12 Enclosure  
**Standard**



## Safety Features

- Anti-Fall Device on  
**Carriage**
- Pressure activated safety  
**stop on carriage**
- CE Compliant, UL, CUL

**ROBOPACUSA.COM**

**INFO.US@ROBOPAC.COM**

